WOVEN BRAKE LININGS

Asbestos Woven Brake Lining

Asbestos Woven Brake Lining is a flexible friction lining woven from brass-wire-reinforced asbestos yarn, for the brakes and clutches of winches, hoists, cranes and heavy machinery. Non-asbestos equivalents with comparable performance are available where required.

It provides a stable coefficient of friction and good heat resistance, and can be drilled and cut to your brake band.

KEY FEATURES

- ✓ Brass-wire-reinforced asbestos yarn construction
- ✓ Stable coefficient of friction around 0.4
- ✓ Good heat resistance, rated to around 350°C
- ✓ Drilled and cut to your brake band pattern
- ✓ Non-asbestos equivalent available where required

SPECIFICATIONS

Material	Brass-reinforced asbestos yarn
Coefficient of Friction	~0.4
Max Temperature	~350°C
Thickness	3 mm to 12 mm
Form	Roll / band, drilled to order
Alternative	Non-asbestos grade available

APPLICATIONS

Winch & hoist brakes · Crane & drum brakes · Band & clutch surfaces · Heavy-machinery braking · High-heat friction duty

INDUSTRIES SERVED

Cranes & Hoists · Steel Mills · Cement Plants · Mining · Oil & Gas

Al-Hamd Traders

28 Brandreth Road, Lahore, Pakistan
info@alhamdtrader.com | 0321 4445067
alhamdtrader.com

Specifications are typical for this product grade. Please confirm exact figures with us before final specification.